

```
PS C:\Program Files\SplunkUniversalForwarder\bin> ./splunk cmd btool inputs list
--debug
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [MonitorNoHandle://C:\Windows\System32\Dns\dns.log]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = MSAD:NT6:DNS
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [SSL]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    allowSslRenegotiation = true
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    cipherSuite =
ECDHE-ECDSA-AES256-GCM-SHA384:ECDHE-RSA-AES256-GCM-SHA384:ECDHE-ECDSA-AES128-GCM-SHA
256:ECDHE-RSA-AES128-GCM-SHA256:ECDHE-ECDSA-AES256-SHA384:ECDHE-RSA-AES256-SHA384:EC
DHE-ECDSA-AES128-SHA256:ECDHE-RSA-AES128-SHA256
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    ecdhCurves = prime256v1, secp384r1, secp521r1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    sslQuietShutdown = false
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    sslVersions = tls1.2
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    [WinEventLog://Application]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    checkpointInterval = 5
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
```

```
        current_only = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
        disabled = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_resolve_ad_obj = 0
host = $decideOnStartup
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        index = wineventlog
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        renderXml = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
        start_from = oldest
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [WinEventLog://DFS Replication]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_resolve_ad_obj = 0
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        renderXml = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [WinEventLog://DNS Server]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
```

```
                evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                evt_resolve_ad_obj = 0
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                interval = 60

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
                renderXml = true

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
                [WinEventLog://Directory Service]

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
                disabled = 1

C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                evt_resolve_ad_obj = 0
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                interval = 60

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
                renderXml = true

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
                [WinEventLog://File Replication Service]

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
                disabled = 1

C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                evt_resolve_ad_obj = 0
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
                interval = 60

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
                renderXml = true

C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
```

```
[WinEventLog://ForwardedEvents]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    checkpointInterval = 5
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    current_only = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    disabled = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    host = WinEventLogForwardHost
C:\Program Files\SplunkUniversalForwarder\etc\apps\_server_app_Windows domain
controllers\local\inputs.conf index = wineventlog
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    renderXml = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    start_from = oldest
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinEventLog://Key Management Service]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    renderXml = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
```

```
[WinEventLog://Security]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    blacklist1 = EventCode="4662" Message="Object
Type:(?!\\s*groupPolicyContainer)"
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    blacklist2 = EventCode="566" Message="Object
Type:(?!\\s*groupPolicyContainer)"
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    checkpointInterval = 5
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    current_only = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    disabled = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    evt_resolve_ad_obj = 1
host = $decideOnStartup
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    index = wineventlog
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    renderXml = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    start_from = oldest
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    [WinEventLog://Setup]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    checkpointInterval = 5
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    current_only = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    disabled = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
```

```
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_resolve_ad_obj = 0
host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\apps\_server_app_Windows domain
controllers\local\inputs.conf index = wineventlog
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
        start_from = oldest
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
        [WinEventLog://System]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
        checkpointInterval = 5
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
        current_only = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
        disabled = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_resolve_ad_obj = 0
host = $decideOnStartup
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        index = wineventlog
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        renderXml = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
        start_from = oldest
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [WinHostMon://Computer]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
host = $decideOnStartup
```

```
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = Computer
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinHostMon://Disk]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = Disk
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinHostMon://Driver]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = Driver
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinHostMon://NetworkAdapter]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = NetworkAdapter
C:\Program
```

```
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinHostMon://OperatingSystem]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = OperatingSystem
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinHostMon://Process]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = Process
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinHostMon://Processor]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = Processor
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinHostMon://Roles]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
```



```
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = Roles
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinHostMon://Service]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = Service
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinNetMon://inbound]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    direction = inbound
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinNetMon://outbound]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    direction = outbound
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinPrintMon://driver]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
```

```
        baseline = 1
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        type = driver
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [WinPrintMon://port]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        baseline = 1
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        type = port
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [WinPrintMon://printer]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        baseline = 1
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        interval = 600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        type = printer
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [WinRegMon://default]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
```

```
                baseline = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    hive = .*
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    proc = .*
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = rename|set|delete|create
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinRegMon://hkcu_run]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    baseline = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    hive =
\\REGISTRY\\USER\\.*\\Software\\Microsoft\\Windows\\CurrentVersion\\Run\\.*
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    proc = .*
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    type = set|create|delete|rename
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [WinRegMon://hk1m_run]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    baseline = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    hive =
```

```
\\REGISTRY\\MACHINE\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\Run\\.*
host = $decideOnStartup
index = default
C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    interval = 60

C:\\Program
Files\\SplunkUniversalForwarder\\etc\\apps\\Splunk_TA_windows\\local\\inputs.conf
    proc = .*

C:\\Program
Files\\SplunkUniversalForwarder\\etc\\apps\\Splunk_TA_windows\\local\\inputs.conf
    type = set|create|delete|rename

C:\\Program
Files\\SplunkUniversalForwarder\\etc\\apps\\SplunkUniversalForwarder\\local\\inputs.conf
    [admon://NearestDC]

C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    baseline = 0

host = $decideOnStartup
index = default
C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    interval = 60

C:\\Program
Files\\SplunkUniversalForwarder\\etc\\apps\\SplunkUniversalForwarder\\local\\inputs.conf
    monitorSubtree = 1

C:\\Program
Files\\SplunkUniversalForwarder\\etc\\apps\\Splunk_TA_windows\\local\\inputs.conf
    [admon://default]

C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    baseline = 0

C:\\Program
Files\\SplunkUniversalForwarder\\etc\\apps\\Splunk_TA_windows\\local\\inputs.conf
    disabled = 0

host = $decideOnStartup
index = default
C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    interval = 60

C:\\Program
Files\\SplunkUniversalForwarder\\etc\\apps\\Splunk_TA_windows\\local\\inputs.conf
    monitorSubtree = 1

C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    [batch://C:\\Program
Files\\SplunkUniversalForwarder\\var\\run\\splunk\\search_telemetry\\*search_telemetry.js
n]
C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    _rcvbuf = 1572864
C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    crcSalt = <SOURCE>
C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    evt_dc_name =
C:\\Program Files\\SplunkUniversalForwarder\\etc\\system\\local\\inputs.conf
    evt_dns_name =
```

```
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = _introspection
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    log_on_completion = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    move_policy = sinkhole
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    sourcetype = search_telemetry
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [batch://C:\Program
Files\SplunkUniversalForwarder\var\spool\splunk]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    crcSalt = <SOURCE>
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    move_policy = sinkhole
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [batch://C:\Program
Files\SplunkUniversalForwarder\var\spool\splunk\...stashhec]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    crcSalt = <SOURCE>
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    move_policy = sinkhole
```

```
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    sourcetype = stash_hec
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [batch://C:\Program
Files\SplunkUniversalForwarder\var\spool\splunk\...stash_new]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    crcSalt = <SOURCE>
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    move_policy = sinkhole
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    queue = stashparsing
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    sourcetype = stash_new
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    time_before_close = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [batch://C:\Program
Files\SplunkUniversalForwarder\var\spool\splunk\tracker.log*]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = _internal
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    move_policy = sinkhole
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    sourcetype = splunkd_latency_tracker
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [blacklist:C:\Program
Files\SplunkUniversalForwarder\etc\auth]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
```

```
        _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        [blacklist:C:\Program
Files\SplunkUniversalForwarder\etc\passwd]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        [fschange:C:\Program Files\SplunkUniversalForwarder\etc]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        delayInMills = 100
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        disabled = false
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        filesPerDelay = 10
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        followLinks = false
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        fullEvent = false
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        hashMaxSize = -1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        host = $decideOnStartup
```

```
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    pollPeriod = 600
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    recurse = true
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    sendEventMaxSize = -1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    signedaudit = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    [http]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    ackIdleCleanup = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    allowSslCompression = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    allowSslRenegotiation = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    dedicatedIoThreads = 2
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    disabled = 1
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    enableSSL = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    maxSockets = 0
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    maxThreads = 0
C:\Program
```



```
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    port = 8088
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    sslVersions = *,-ssl2
C:\Program
Files\SplunkUniversalForwarder\etc\apps\splunk_httpinput\default\inputs.conf
    useDeploymentServer = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [monitor://C:\Program
Files\SplunkUniversalForwarder\etc\splunk.version]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _TCP_ROUTING = *
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = _internal
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    sourcetype = splunk_version
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [monitor://C:\Program
Files\SplunkUniversalForwarder\var\log\Splunk_TA_windows\WindowsUpdate.log]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = WindowsUpdateLog
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
```

```
[monitor://C:\Program
Files\SplunkUniversalForwarder\var\log\splunk]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = _internal
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [monitor://C:\Program
Files\SplunkUniversalForwarder\var\log\splunk\license_usage_summary.log]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = _telemetry
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\default\inputs.conf
    [monitor://C:\Program
Files\SplunkUniversalForwarder\var\log\splunk\metrics.log]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\default\inputs.conf
    _TCP_ROUTING = *
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\default\inputs.conf
    index = _internal
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
```

```
[monitor://C:\Program
Files\SplunkUniversalForwarder\var\log\splunk\splunk_instrumentation_cloud.log*]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = _telemetry
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    sourcetype = splunk_cloud_telemetry
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\default\inputs.conf
    [monitor://C:\Program
Files\SplunkUniversalForwarder\var\log\splunk\splunkd.log]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\default\inputs.conf
    _TCP_ROUTING = *
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\default\inputs.conf
    index = _internal
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [monitor://C:\Program
Files\SplunkUniversalForwarder\var\log\watchdog\watchdog.log*]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
```

```
index = _internal
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [monitor://C:\Windows\System32\DHCP]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    crcSalt = <SOURCE>
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = DhcpSrvLog
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    whitelist = DhcpSrvLog*
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [monitor://C:\Windows\WindowsUpdate.log]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = WindowsUpdateLog
C:\Program
```

```
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [monitor://C:\Windows\debug\netlogon.log]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = MSAD:NT6:Netlogon
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    [perfmon://Available Memory]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    counters = Available Bytes
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    object = Memory
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [perfmon://CPU]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    counters = % Processor Time; % User Time; % Privileged Time;
Interrupts/sec; % DPC Time; % Interrupt Time; DPCs Queued/sec; DPC Rate; % Idle
Time; % C1 Time; % C2 Time; % C3 Time; C1 Transitions/sec; C2 Transitions/sec; C3
Transitions/sec
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
```

```
instances = *
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
object = Processor
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
[perfmon://CPU Load]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
counters = % Processor Time;% User Time
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
instances = _Total
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
object = Processor
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
[perfmon://DFS_Replicated_Folders]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
counters = Bandwidth Savings Using DFS Replication; RDC Bytes Received;
RDC Compressed Size of Files Received; RDC Size of Files Received; RDC Number of
Files Received; Compressed Size of Files Received; Size of Files Received; Total
Files Received; Deleted Space In Use; Deleted Bytes Cleaned up; Deleted Files
Cleaned up; Deleted Bytes Generated; Deleted Files Generated; Updates Dropped; File
Installs Retried; File Installs Succeeded; Conflict Folder Cleanups Completed;
Conflict Space In Use; Conflict Bytes Cleaned up; Conflict Files Cleaned up;
Conflict Bytes Generated; Conflict Files Generated; Staging Space In Use; Staging
Bytes Cleaned up; Staging Files Cleaned up; Staging Bytes Generated; Staging Files
Generated
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
disabled = 1
host = $decideOnStartup
index = default
```

```
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    instances = *
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 30
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    object = DFS Replicated Folders
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [perfmon://DNS]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    counters = Total Query Received; Total Query Received/sec; UDP Query
Received; UDP Query Received/sec; TCP Query Received; TCP Query Received/sec; Total
Response Sent; Total Response Sent/sec; UDP Response Sent; UDP Response Sent/sec;
TCP Response Sent; TCP Response Sent/sec; Recursive Queries; Recursive Queries/sec;
Recursive Send TimeOuts; Recursive TimeOut/sec; Recursive Query Failure; Recursive
Query Failure/sec; Notify Sent; Zone Transfer Request Received; Zone Transfer
Success; Zone Transfer Failure; AXFR Request Received; AXFR Success Sent; IXFR
Request Received; IXFR Success Sent; Notify Received; Zone Transfer SOA Request
Sent; AXFR Request Sent; AXFR Response Received; AXFR Success Received; IXFR Request
Sent; IXFR Response Received; IXFR Success Received; IXFR UDP Success Received; IXFR
TCP Success Received; WINS Lookup Received; WINS Lookup Received/sec; WINS Response
Sent; WINS Response Sent/sec; WINS Reverse Lookup Received; WINS Reverse Lookup
Received/sec; WINS Reverse Response Sent; WINS Reverse Response Sent/sec; Dynamic
Update Received; Dynamic Update Received/sec; Dynamic Update NoOperation; Dynamic
Update NoOperation/sec; Dynamic Update Written to Database; Dynamic Update Written
to Database/sec; Dynamic Update Rejected; Dynamic Update TimeOuts; Dynamic Update
Queued; Secure Update Received; Secure Update Received/sec; Secure Update Failure;
Database Node Memory; Record Flow Memory; Caching Memory; UDP Message Memory; TCP
Message Memory; Nostat Memory; Unmatched Responses Received
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    mode = multikv
```

```
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    object = DNS
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    [perfmon://Free Disk Space]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    counters = Free Megabytes;% Free Space
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    instances = _Total
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    interval = 3600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    object = LogicalDisk
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [perfmon://LogicalDisk]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    counters = % Free Space; Free Megabytes; Current Disk Queue Length; %
Disk Time; Avg. Disk Queue Length; % Disk Read Time; Avg. Disk Read Queue Length; %
Disk Write Time; Avg. Disk Write Queue Length; Avg. Disk sec/Transfer; Avg. Disk
sec/Read; Avg. Disk sec/Write; Disk Transfers/sec; Disk Reads/sec; Disk Writes/sec;
Disk Bytes/sec; Disk Read Bytes/sec; Disk Write Bytes/sec; Avg. Disk Bytes/Transfer;
Avg. Disk Bytes/Read; Avg. Disk Bytes/Write; % Idle Time; Split IO/Sec
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    instances = *
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
```



```
        object = LogicalDisk
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [perfmon://Memory]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        counters = Page Faults/sec; Available Bytes; Committed Bytes; Commit
Limit; Write Copies/sec; Transition Faults/sec; Cache Faults/sec; Demand Zero
Faults/sec; Pages/sec; Pages Input/sec; Page Reads/sec; Pages Output/sec; Pool Paged
Bytes; Pool Nonpaged Bytes; Page Writes/sec; Pool Paged Allocs; Pool Nonpaged
Allocs; Free System Page Table Entries; Cache Bytes; Cache Bytes Peak; Pool Paged
Resident Bytes; System Code Total Bytes; System Code Resident Bytes; System Driver
Total Bytes; System Driver Resident Bytes; System Cache Resident Bytes; % Committed
Bytes In Use; Available KBytes; Available MBytes; Transition Pages RePurposed/sec;
Free & Zero Page List Bytes; Modified Page List Bytes; Standby Cache Reserve Bytes;
Standby Cache Normal Priority Bytes; Standby Cache Core Bytes; Long-Term Average
Standby Cache Lifetime (s)
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        object = Memory
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [perfmon://NTDS]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        counters = DRA Inbound Properties Total/sec; AB Browsers/sec; DRA Inbound
Objects Applied/sec; DS Threads in Use; AB Client Sessions; DRA Pending Replication
Synchronizations; DRA Inbound Object Updates Remaining in Packet; DS Security
Descriptor sub-operations/sec; DS Security Descriptor Propagations Events; LDAP
Client Sessions; LDAP Active Threads; LDAP Writes/sec; LDAP Searches/sec; DRA
Outbound Objects/sec; DRA Outbound Properties/sec; DRA Inbound Values Total/sec; DRA
Sync Requests Made; DRA Sync Requests Successful; DRA Sync Failures on Schema
Mismatch; DRA Inbound Objects/sec; DRA Inbound Properties Applied/sec; DRA Inbound
```

Properties Filtered/sec; DS Monitor List Size; DS Notify Queue Size; LDAP UDP operations/sec; DS Search sub-operations/sec; DS Name Cache hit rate; DRA Highest USN Issued (Low part); DRA Highest USN Issued (High part); DRA Highest USN Committed (Low part); DRA Highest USN Committed (High part); DS % Writes from SAM; DS % Writes from DRA; DS % Writes from LDAP; DS % Writes from LSA; DS % Writes from KCC; DS % Writes from NSPI; DS % Writes Other; DS Directory Writes/sec; DS % Searches from SAM; DS % Searches from DRA; DS % Searches from LDAP; DS % Searches from LSA; DS % Searches from KCC; DS % Searches from NSPI; DS % Searches Other; DS Directory Searches/sec; DS % Reads from SAM; DS % Reads from DRA; DRA Inbound Values (DNs only)/sec; DRA Inbound Objects Filtered/sec; DS % Reads from LSA; DS % Reads from KCC; DS % Reads from NSPI; DS % Reads Other; DS Directory Reads/sec; LDAP Successful Binds/sec; LDAP Bind Time; SAM Successful Computer Creations/sec: Includes all requests; SAM Machine Creation Attempts/sec; SAM Successful User Creations/sec; SAM User Creation Attempts/sec; SAM Password Changes/sec; SAM Membership Changes/sec; SAM Display Information Queries/sec; SAM Enumerations/sec; SAM Transitive Membership Evaluations/sec; SAM Non-Transitive Membership Evaluations/sec; SAM Domain Local Group Membership Evaluations/sec; SAM Universal Group Membership Evaluations/sec; SAM Global Group Membership Evaluations/sec; SAM GC Evaluations/sec; DRA Inbound Full Sync Objects Remaining; DRA Inbound Bytes Total/sec; DRA Inbound Bytes Not Compressed (Within Site)/sec; DRA Inbound Bytes Compressed (Between Sites, Before Compression)/sec; DRA Inbound Bytes Compressed (Between Sites, After Compression)/sec; DRA Outbound Bytes Total/sec; DRA Outbound Bytes Not Compressed (Within Site)/sec; DRA Outbound Bytes Compressed (Between Sites, Before Compression)/sec; DRA Outbound Bytes Compressed (Between Sites, After Compression)/sec; DS Client Binds/sec; DS Server Binds/sec; DS Client Name Translations/sec; DS Server Name Translations/sec; DS Security Descriptor Propagator Runtime Queue; DS Security Descriptor Propagator Average Exclusion Time; DRA Outbound Objects Filtered/sec; DRA Outbound Values Total/sec; DRA Outbound Values (DNs only)/sec; AB ANR/sec; AB Property Reads/sec; AB Searches/sec; AB Matches/sec; AB Proxy Lookups/sec; ATQ Threads Total; ATQ Threads LDAP; ATQ Threads Other; DRA Inbound Bytes Total Since Boot; DRA Inbound Bytes Not Compressed (Within Site) Since Boot; DRA Inbound Bytes Compressed (Between Sites, Before Compression) Since Boot; DRA Inbound Bytes Compressed (Between Sites, After Compression) Since Boot; DRA Outbound Bytes Total Since Boot; DRA Outbound Bytes Not Compressed (Within Site) Since Boot; DRA Outbound Bytes Compressed (Between Sites, Before Compression) Since Boot; DRA Outbound Bytes Compressed (Between Sites, After Compression) Since Boot; LDAP New Connections/sec; LDAP Closed Connections/sec; LDAP New SSL Connections/sec; DRA Pending Replication Operations; DRA Threads Getting NC Changes; DRA Threads Getting NC Changes Holding Semaphore; DRA Inbound Link Value Updates Remaining in Packet; DRA Inbound Total Updates Remaining in Packet; DS % Writes from NTDSAPI; DS % Searches from NTDSAPI; DS % Reads from NTDSAPI; SAM Account Group Evaluation Latency; SAM Resource Group Evaluation Latency; ATQ Outstanding Queued Requests; ATQ Request Latency; ATQ Estimated Queue Delay; Tombstones Garbage Collected/sec; Phantoms Cleaned/sec; Link Values Cleaned/sec; Tombstones Visited/sec; Phantoms Visited/sec; NTLM Binds/sec; Negotiated Binds/sec; Digest Binds/sec; Simple Binds/sec; External Binds/sec; Fast Binds/sec; Base searches/sec; Subtree searches/sec; Onelevel searches/sec; Database adds/sec; Database modifies/sec; Database deletes/sec; Database recycles/sec; Approximate highest DNT; Transitive operations/sec; Transitive suboperations/sec; Transitive operations milliseconds run C:\Program

```
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    object = NTDS
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [perfmon://Network]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    counters = Bytes Total/sec; Packets/sec; Packets Received/sec; Packets
Sent/sec; Current Bandwidth; Bytes Received/sec; Packets Received Unicast/sec;
Packets Received Non-Unicast/sec; Packets Received Discarded; Packets Received
Errors; Packets Received Unknown; Bytes Sent/sec; Packets Sent Unicast/sec; Packets
Sent Non-Unicast/sec; Packets Outbound Discarded; Packets Outbound Errors; Output
Queue Length; Offloaded Connections; TCP Active RSC Connections; TCP RSC Coalesced
Packets/sec; TCP RSC Exceptions/sec; TCP RSC Average Packet Size
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    instances = *
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    object = Network Interface
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
```

```
[perfmon://Network Interface]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    counters = Bytes Received/sec;Bytes Sent/sec
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    instances = *
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\SplunkUniversalForwarder\local\inputs.conf
    object = Network Interface
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [perfmon://Network_Interface]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    counters = Bytes Total/sec; Packets/sec; Packets Received/sec; Packets
Sent/sec; Current Bandwidth; Bytes Received/sec; Packets Received Unicast/sec;
Packets Received Non-Unicast/sec; Packets Received Discarded; Packets Received
Errors; Packets Received Unknown; Bytes Sent/sec; Packets Sent Unicast/sec; Packets
Sent Non-Unicast/sec; Packets Outbound Discarded; Packets Outbound Errors; Output
Queue Length; Offloaded Connections; TCP Active RSC Connections; TCP RSC Coalesced
Packets/sec; TCP RSC Exceptions/sec; TCP RSC Average Packet Size
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    instances = *
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    object = Network Interface
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [perfmon://PhysicalDisk]
```

```
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    counters = Current Disk Queue Length; % Disk Time; Avg. Disk Queue
Length; % Disk Read Time; Avg. Disk Read Queue Length; % Disk Write Time; Avg. Disk
Write Queue Length; Avg. Disk sec/Transfer; Avg. Disk sec/Read; Avg. Disk sec/Write;
Disk Transfers/sec; Disk Reads/sec; Disk Writes/sec; Disk Bytes/sec; Disk Read
Bytes/sec; Disk Write Bytes/sec; Avg. Disk Bytes/Transfer; Avg. Disk Bytes/Read;
Avg. Disk Bytes/Write; % Idle Time; Split IO/Sec
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    instances = *
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    object = PhysicalDisk
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [perfmon://Process]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    counters = % Processor Time; % User Time; % Privileged Time; Virtual
Bytes Peak; Virtual Bytes; Page Faults/sec; Working Set Peak; Working Set; Page File
Bytes Peak; Page File Bytes; Private Bytes; Thread Count; Priority Base; Elapsed
Time; ID Process; Creating Process ID; Pool Paged Bytes; Pool Nonpaged Bytes; Handle
Count; IO Read Operations/sec; IO Write Operations/sec; IO Data Operations/sec; IO
Other Operations/sec; IO Read Bytes/sec; IO Write Bytes/sec; IO Data Bytes/sec; IO
Other Bytes/sec; Working Set - Private
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    instances = *
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
```

```
        interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        object = Process
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [perfmon://Processor]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        counters = % Processor Time; % User Time; % Privileged Time;
Interrupts/sec; % DPC Time; % Interrupt Time; DPCs Queued/sec; DPC Rate; % Idle
Time; % C1 Time; % C2 Time; % C3 Time; C1 Transitions/sec; C2 Transitions/sec; C3
Transitions/sec
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
host = $decideOnStartup
index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        instances = *
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        interval = 10
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        mode = multikv
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        object = Processor
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        useEnglishOnly = true
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [perfmon://ProcessorInformation]
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        counters = % Processor Time; Processor Frequency
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
host = $decideOnStartup
index = default
```

```
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    instances = *

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 10

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    mode = multikv

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    object = Processor Information

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    useEnglishOnly = true

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [perfmon://System]

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    counters = File Read Operations/sec; File Write Operations/sec; File
Control Operations/sec; File Read Bytes/sec; File Write Bytes/sec; File Control
Bytes/sec; Context Switches/sec; System Calls/sec; File Data Operations/sec; System
Up Time; Processor Queue Length; Processes; Threads; Alignment Fixups/sec; Exception
Dispatches/sec; Floating Emulations/sec; % Registry Quota In Use

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1

host = $decideOnStartup
index = default

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    instances = *

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 10

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    mode = multikv

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    object = System

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    useEnglishOnly = true

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [powershell://AD-Health]

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
```

```
        disabled = 1
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        interval = 60

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        schedule = 0 */5 * ? * *

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        script = &
"$SplunkHome\etc\apps\Splunk_TA_windows\bin\Invoke-MonitoredScript.ps1" -Command
".\powershell\2012r2-health.ps1"

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        source = Powershell

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        sourcetype = MSAD:NT6:Health

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [powershell://Replication-Stats]

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        interval = 60

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        schedule = 0 */5 * ? * *

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        script = &
"$SplunkHome\etc\apps\Splunk_TA_windows\bin\Invoke-MonitoredScript.ps1" -Command
".\powershell\2012r2-repl-stats.ps1"

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        source = Powershell

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        sourcetype = MSAD:NT6:Replication

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [powershell://Siteinfo]

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
host = $decideOnStartup
```



```
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    schedule = 0 15 * ? * *

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    script = &
"$SplunkHome\etc\apps\Splunk_TA_windows\bin\Invoke-MonitoredScript.ps1" -Command
".\powershell\2012r2-siteinfo.ps1"

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    source = Powershell

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = MSAD:NT6:SiteInfo

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [powershell://generate_windows_update_logs]

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
host = $decideOnStartup
index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    interval = 60

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    schedule = 0 */24 * * *

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    script =
."$SplunkHome\etc\apps\Splunk_TA_windows\bin\powershell\generate_windows_update_logs
.ps1"
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [script]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
```

```
        interval = 60.0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        start_by_shell = false
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        [script://C:\Program
Files\SplunkUniversalForwarder\bin\scripts\splunk-wmi.path]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        disabled = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        interval = 10000000
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        persistentQueueSize = 200MB
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        queue = winparsing
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        source = wmi
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        sourcetype = wmi
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\netsh_address.bat]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
        disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
        index = default
C:\Program
```

```
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 86400
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = Script:NetworkConfiguration
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\runpowershell.cmd
dns-health.ps1]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 3600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    source = Powershell
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = MSAD:NT6:DNS-Health
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\runpowershell.cmd
dns-zoneinfo.ps1]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
```

```
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 3600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    source = Powershell
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = MSAD:NT6:DNS-Zone-Information
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\runpowershell.cmd
nt6-health.ps1]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 300
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    source = Powershell
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = MSAD:NT6:Health
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\runpowershell.cmd
nt6-repl-stat.ps1]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
```

```
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 300
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    source = Powershell
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = MSAD:NT6:Replication
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\runpowershell.cmd
nt6-siteinfo.ps1]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 3600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    source = Powershell
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = MSAD:NT6:SiteInfo
```

```
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\win_installed_apps.bat
]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 86400

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = Script:InstalledApps

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\win_listening_ports.ba
t]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default

C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 3600

C:\Program
```

```
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = Script:ListeningPorts
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\win_timesync_configura
tion.bat]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    interval = 3600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = Script:TimesyncConfiguration
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    [script://C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\bin\win_timesync_status.ba
t]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    disabled = 1
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
```

```
interval = 3600
C:\Program
Files\SplunkUniversalForwarder\etc\apps\Splunk_TA_windows\local\inputs.conf
    sourcetype = Script:TimesyncStatus
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [splunktcp]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    acceptFrom = *
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    connection_host = ip
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    route =
has_key:_replicationBucketUUID:replicationQueue;has_key:_dstx:typingQueue;has_key:_
linebreaker:indexQueue;absent_key:_linebreaker:parsingQueue
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [tcp]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    acceptFrom = *
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    connection_host = dns
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    [udp]
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    _rcvbuf = 1572864
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    connection_host = ip
```



```
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dc_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_dns_name =
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    evt_resolve_ad_obj = 0
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    host = $decideOnStartup
C:\Program Files\SplunkUniversalForwarder\etc\system\local\inputs.conf
    index = default
PS C:\Program Files\SplunkUniversalForwarder\bin>
```